



# NACHI BEARINGS TRAINING INDUSTRY

## TYPE TS



## Timken Im67048 Cylindrical Roller Bearings

Bearing No. Im67048

Im67048 Bearing 2D drawings and 3D CAD models

|   |               |
|---|---------------|
| Series  | LM67000       |
| Cone Part Number  | LM67048       |
| Design Units  | Imperial      |
| Cage Type   | Stamped Steel |
| C1 - Dynamic Radial Rating (Two-Row, 1 million revolutions) <sup>1</sup>      | 18300 lbf     |
| C90(2) - Dynamic Radial Rating (Two-Row, 90 million revolutions) <sup>2</sup> | 4740 lbf      |
| d   | 1.2500 in     |
| B - Cone Width  | 0.6600 in     |
| R - Cone Backface To Clear Radius <sup>3</sup>                                | 0.14 in       |
| da - Cone Frontface Backing Diameter  | 1.42 in       |
| db - Cone Backface Backing Diameter   | 1.67 in       |
| Ab - Cage-Cone Frontface Clearance  | 0.05 in       |
| Aa - Cage-Cone Backface Clearance   | 0.01 in       |
| a - Effective Center Location <sup>4</sup>                                    | -0.12 in      |
| C90 - Dynamic Radial Rating (90 million revolutions) <sup>5</sup>             | 2720 lbf      |
| C1 - Dynamic Radial Rating (1 million revolutions) <sup>6</sup>               | 10500 lbf     |
| C0 - Static Radial Rating   | 10000 lbf     |
|   |               |



## NACHI BEARINGS TRAINING INDUSTRY

|   |          |
|---|----------|
| $C_{a90}$ - Dynamic Thrust Rating (90 million revolutions) <sup>7</sup> | 1920 lbf |
| K - Factor <sup>8</sup>   | 1.42     |
| G1 - Heat Generation Factor (Roller-Raceway)                            | 12.8     |
| G2 - Heat Generation Factor (Rib-Roller End)                            | 9.93     |
| Cg - Geometry Factor  | 0.0612   |